





MOUNTING DETAIL

$\begin{bmatrix} 15 \\ [382] \end{bmatrix}$ $\begin{bmatrix} 24\frac{1}{4} \\ [743] \end{bmatrix}$

INSTALLATION INSTRUCTIONS:

- A. PROVIDE WALL WITH ADEQUATE BACKING (1) TO MOUNT CABINET.
- B. DRILL HOUSING (2) TO LOCATE MOUNTING POINTS WHERE BACKING EXISTS. REMOVE HOUSING (2) AND INSTALL WALL ANCHORS (3) (BY OTHERS) AS REQUIRED FOR WALL TYPE CONSTRUCTION.
- C. INSTALL FIRE EXTINGUISHER HOUSING (2) ONTO THE WALL (1).
- D. FASTEN FIRE EXTINGUISHER HOUSING (2) ONTO THE WALL USING SCREWS (BY OTHERS) TO SUIT WALL CONSTRUCTION.

IMPORTANT! AFTER INSTALLATION, ALL JOINTS REQUIRE SECURITY SEALANT BY INSTALLER TO ELIMINATE GAPS BETWEEN WALL AND FIXTURE.

LOCATE ITEM TO CONFORM WITH APPLICABLE CODES FOR ACCESSIBILITY.



NOTE: WEIGHT WITHOUT FIRE EXTINGUISHER = 15.5 lbs.

WHITEHALL MANUFACTURING
P.O. BOX 3527 Industry, CA 91744
15125 Proctor Ave Industry, CA 91746
(626) 968-6681 FAX (626) 855-4862

LIGATURE RESISTANT SURFACE MOUNT EXTINGUISHER CABINET WH1754-A

(2)

MANUFACTURE DATE

AUGUST 2018

TO PRESENT

DATE ISSUED 10/12/2022 DRAWING NUMBER

DATE REVISED

9918-137-001