

### **Hi-Boy Whirlpools**

Division of Acorn Engineering Company







Use



## H Series 105 Gallon Mobile Whirlpool

H-105-M



H-105-M

Whitehall H-105-M Mobile Whirlpools are recommended for shallow or deep body immersion offering complete coverage of extremities as well as the entire back and shoulder area with greater patient comfort.

Tank Capacity is 105 gallons.

**Whirlpool Tank** is 48"L x 24"W x 28"D and is seamless welded construction, fabricated from heavy gauge, type 304 stainless steel, polished to a satin finish. Tank rim is reinforced with a concealed stainless steel rod. Tank bottom is a seamless, coved (rounded) design for effective cleaning.

**Heavy Duty Swivel Casters** support all mobile models. Rear pair of casters are lockable for stabilizing Whirlpool during use.

**Turbine Raising and Lowering Device** permits adjustment of desired height and direction of water agitation towards the area of the body during Whirlpool use. It is spring balanced and provided with a locking device.

**Turbine Assembly** functions both as agitator and emptying device. It is equipped with Underwriters Laboratory listed 1/2 HP jet pump motor protected with an ABS plastic shell, automatic thermal overload protector, and lifetime-sealed bearings. All parts contacting the water are stainless steel, chrome plated brass or bronze.

**Drain option -SDP** has a bottom drain, leading to a separate, concealed water evacuation pump. A hose is attached to the side of the unit to facilitate the evacuation.

**Thermometer** is provided with a dual scale, adjustable calibration, and a stem inserts into a retainer to prevent rattle during whirlpool agitation.

#### **GUIDE SPECIFICATIONS**

Provide Whitehall Mobile Whirlpool (specify model number and options) with a 105-gallon capacity, 48"L x 24"W x 28"D. Whirlpool shall be fabricated from heavy gauge, type 304 stainless steel. Construction shall be seamless welded and exposed surfaces shall be polished to satin finish. Bottom of tank shall be a seamless, rounded coved design. Whirlpool shall have heavy duty swivel casters with locking device on rear pair of casters. Provide a turbine assembly with raising and lowering device which functions both as agitator and emptying device, permits adjustment of desired height, direction of water agitation, and can be locked into place. Turbine assembly shall be UL listed 1/2 HP jet pump motor with automatic thermal overload protector and lifetime-sealed bearings. Provide a thermometer with a stem retainer to prevent rattling when whirlpool is in operation.

Please visit www.whitehallmfg.com for most current specifications.





### **Hi-Boy Whirlpools**

# MODEL NUMBER AND OPTION SELECTIONS Series ☑ H Hi-Boy Series Capacity ☑ -105 Gallons

### **Type ☑** -M Mobile Whirlpool

# Turbine Electrical Requirements □ 115VAC / 50Hz □ 230VAC / 50Hz □ 230VAC / 60HZ

Country of Use \_\_\_\_\_

### For Mixing Valve:

Refer to supplemental MXT15-OTG and DU-1 sheet for details.

**Suffix Options** (See Whirlpool Options Section for Details)

☐ -ADH Auxiliary Drain Hose Assembly
☐ -AS2 Adjustable Suspension Seat

☐ -AS2 Adjustable Suspension Seat
☐ -EG Enviro-Glaze<sup>®</sup> Color Powder Coating -

Specify Color:

https://www.whitehallmfg.com/enviro-glaze


☐ -GFI Ground Fault Interrupter

-LOGO Applied Logos: Team, Facility, Company

Logo

☐ -SDP Separate Drain Pump

☐ -TTS2 Tank Top Seat



All dimensions are nominal and subject to manufacturer's change without notice. Whitehall assumes no responsibility fo use of void or superseded data @ Whitehall Manufacturing, Member of Morris Group International.

Please visit **www.whitehallmfg.com** for most current specifications.

Whitehall Mfg. • P.O. Box 3527 • City of Industry, CA 91744 • (800) 591-9280 • (626) 968-6681